



# SAFETY TEST REPORT

## MEASUREMENT AND TEST REPORT

For

Shenzhen Key Smart Limited.

406-407 Jinqi Zhigu Building, 4F Tangling Road, Nanshan District, Shenzhen City.

**Models: See below**

November 16, 2018

<b>This Report Concerns:</b> <input checked="" type="checkbox"/> Original Report	<b>Equipment Type:</b> Smart Watch
<b>Test Standard:</b>	EN 60950-1:2006 + A11:2009 + A1:2010 + A12: 2011+A2:2013
<b>Report Number:</b>	CTB181116035RS
<b>Test Date:</b>	November 08-15, 2018
<b>Test category:</b>	Consignment test
<b>Prepared By:</b>	<b>Shenzhen CTB Testing Technology Co., Ltd.</b>  Floor 1&2, Building E, No. 26 of Xinhe Road, Xinqiao Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, China.  Tel: 4008-258-120 E-mail: <a href="mailto:ctb@ctb-lab.com">ctb@ctb-lab.com</a> Web: <a href="http://www.ctb-lab.com">http://www.ctb-lab.com</a>

**Note:** This test report is limited to the above client company and the product model only. It may not be duplicated without prior written consent of Shenzhen CTB Testing Technology Co., Ltd.

<b>TEST REPORT</b> <b>EN60950 -1</b> <b>Information technology equipment – Safety –</b> <b>Part 1: General requirements</b>	
Report reference No. ....	: CTB181116035RS
Date of issue.....	: November 16, 2018
<b>Testing laboratory</b>	
Name.....	: Shenzhen CTB Testing Technology Co., Ltd.
Address.....	: F Floor 1&2, Building E, No. 26 of Xinhe Road, Xinqiao Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, China
<b>Client</b>	
Name.....	: Shenzhen Key Smart Limited.
Address.....	: 406-407 Jinqi Zhigu Building, 4F Tangling Road, Nanshan District, Shenzhen City.
<b>Test specification</b>	
Standard.....	: EN 60950-1:2006 + A11:2009 + A1:2010 + A12: 2011+A2:2013
Test procedure.....	: CE-RED
Procedure deviation.....	: N.A.
Non-standard test method..	: N.A.
<b>Test Report Form No.....</b>	: IECEN60950_1F
TRF originator .....	: SGS Fimko Ltd
Master TRF .....	: 2014-02
<b>Copyright © 2006 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.</b> This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
<b>Test item</b>	
Description .....	: Smart Watch
Model No. ....	: Uwatch, Uwatch2, Uwatch3
Trade Mark.....	: UMIDIGI
Manufacturer.....	: Shenzhen Key Smart Limited.
Address.....	: 406-407 Jinqi Zhigu Building, 4F Tangling Road, Nanshan District, Shenzhen City.
Rating(s).....	: Built-in Li battery: 3.7V $\text{---}$ 180mAh Input voltage: 5V $\text{---}$ 1A

**Test item particulars:**

Equipment mobility .....: ☐movable ☒ hand-held ☐transportable  
☐stationary ☐for building-in ☐direct plug-in

Connection to the mains.....: ☐ pluggable equipment ☐ direct plug-in  
☐ permanent connection ☐ for building-in  
☒ not directly connected to the mains

Operating condition .....: ☒ continuous ☐ short-time ☐ intermittent

Over voltage category .....: ☐ OVC I ☒ OVC II ☐ OVC III ☐ OVC IV

Mains supply tolerance (%).....: N/A

Tested for IT power systems .....: ☐ Yes ☒ No

IT testing, phase-phase voltage (V) .....: N/A

Class of equipment .....: ☐ Class I ☐ Class II ☒ Class III  
☐ Not classified

Mass of equipment (kg).....: Main body:0.2Kg

Considered current rating of protective device as part of the building installation (A) (IEC/EN 60950-1/A1) .: N/A

Pollution degree .....: ☒ PD 2 ☐ PD 3

IP protection class .....: IPX0

**Possible test case verdicts:**

- test case does not apply to the test object .....: N (/A)

- test object does meet the requirement .....: P (Pass)

- test object does not meet the requirement .....: F (Fail)

**Testing:**

Date of receipt of test item .....: November 08

Date(s) of performance of tests.....: November 08-15, 2018

**General remarks:**

The test results presented in this report relate only to the object tested.  
This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

"(see Enclosure #)" refers to additional information appended to the report.

"(see appended table)" refers to a table appended to the report.

Throughout this report a ☐ comma / ☒ point is used as the decimal separator.

**General product information:**

- Instructions and equipment marking related to safety is applied in the language that is acceptable in the country in which the equipment is to be sold.
- The product was submitted and tested for use at the ambient temperature (Tma) of 25 °C. for no declaration from manufacturer
- The structure of these models, the working principle and the main components listed in Annex I are the same. The only difference is the appearance of the decoration and the color. All tests were performed on **Uwatch**.

**Copy of marking plate:**

Product Name : Smart Watch

Model No: Uwatch

Rating: Input:5V===1A



Shenzhen Key Smart Limited.

**MADE IN CHINA****Summary of testing:**

The submitted sample were tested and found to compliance with requirements of the standards  
EN 60950-1:2006 + A11:2009 + A1:2010 + A12: 2011+A2:2013

**Testing procedure and testing location**

Laboratory name..... : Shenzhen CTB Testing Technology Co., Ltd.

Testing location/address: : Floor 1&2, Building E, No. 26 of Xinhe Road, Xinqiao Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, China.

Testing Iprocedure : TL ☒ RMT ☐ SMT ☐ WMT ☐ TMP ☐

Tested By : Long Dai  
(Test Engineer)

Reviewed By : Penty Zhang  
(Supervisor)

Approved By : Simon Lee  
(Chief Engineer)



EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

1	GENERAL		P
---	---------	--	---

1.5	Components		P
1.5.1	General	(see appended table 1.5.1)	P
	Comply with IEC 60950 or relevant component standard	Components that were found to affect safety aspects comply with the requirements of this standard or within the safety aspects of the relevant IEC component standards.	P
1.5.2	Evaluation and testing of components	Components that are certified to IEC and /or national standards are used correctly within their ratings. Components not covered by IEC standards are tested under the conditions present in the equipment.	P
1.5.3	Thermal controls		-
1.5.4	Transformers		N
1.5.5	Interconnecting cables		-
1.5.6	Capacitors bridging insulation		-
1.5.7	Resistors bridging insulation		-
1.5.7.1	Resistors bridging functional, basic or supplementary insulation		-
1.5.7.2	Resistors bridging double or reinforced insulation between a.c. mains and other circuits		-
1.5.7.3	Resistors bridging double or reinforced insulation between a.c. mains and antenna or coaxial cable		-
1.5.8	Components in equipment for IT power systems		-
1.5.9	Surge suppressors		-
1.5.9.1	General		-
1.5.9.2	Protection of VDRs	No such parts	-
1.5.9.3	Bridging of functional insulation by a VDR		-
1.5.9.4	Bridging of basic insulation by a VDR		-
1.5.9.5	Bridging of supplementary, double or reinforced insulation by a VDR		-

1.6	Power interface		P
1.6.1	AC power distribution systems	Class III equipment	N
1.6.2	Input current	(See appended table 1.6.2)	P
1.6.3	Voltage limit of hand-held equipment	<250V	P

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.6.4	Neutral conductor		N
1.7	Marking and instructions		P
1.7.1	Power rating and identification markings		P
1.7.1.1	Power rating marking		P
	Multiple mains supply connections (IEC/EN 60950-1 /A1) .....		N
	Rated voltage(s) or voltage range(s) (V) .....	5V	P
	Symbol for nature of supply, for d.c. only .....	 or dc	P
	Rated frequency or rated frequency range (Hz) :		N
	Rated current (mA or A) .....	1A	P
1.7.1.2	Identification markings(IEC/EN 60950-1 /A1).... :		P
	Manufacturer's name or trade-mark or identification mark .....	UMIDIGI	P
	Model identification or type reference .....		P
	Symbol for Class II equipment only .....	Class III appliance	N
	Other markings and symbols .....	Additional symbols or marking does not give rise to misunderstanding.	P
1.7.2	Safety instructions and marking	Safety instruction provided.	P
1.7.2.1	General		N
1.7.2.2	Disconnect devices		N
1.7.2.3	Overcurrent protective device		N
1.7.2.4	IT power distribution systems		N
1.7.2.5	Operator access with a tool	No such operator access area	N
1.7.2.6	Ozone	No ozone produced.	N
1.7.3	Short duty cycles	Continuous operation.	N
1.7.4	Supply voltage adjustment .....	No adjustment used	N
	Methods and means of adjustment; reference to installation instructions .....		N
1.7.5	Power outlets on the equipment .....		N
1.7.6	Fuse identification (marking, special fusing characteristics, cross-reference) .....	No fuse.	N
1.7.7	Wiring terminals	See below	N
1.7.7.1	Protective earthing and bonding terminals .....	Class III equipment, no protective earthing	N
1.7.7.2	Terminals for a.c. mains supply conductors		N
1.7.7.3	Terminals for d.c. mains supply conductors		N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
1.7.8	Controls and indicators	See below	P
1.7.8.1	Identification, location and marking .....		P
1.7.8.2	Colours .....	No such parts used	N
1.7.8.3	Symbols according to IEC 60417 .....		P
1.7.8.4	Markings using figures .....	No figures used.	N
1.7.9	Isolation of multiple power sources .....	Class III appliance	N
1.7.10	Thermostats and other regulating devices .....	No thermostats provided.	N
1.7.11	Durability	The label was rubbed with cloth soaked with water for 15 sec. And then again for 15 sec. With the cloth soaked with petroleum spirit. After this test there was no damage to the label. The marking on the label did not fade. There was no curling and lifting of the label edge.	P
1.7.12	Removable parts	Marking is not placed on removable parts.	P
1.7.13	Replaceable batteries .....	No replaceable batteries used	N
	Language(s) .....		—
1.7.14	Equipment for restricted access locations .....	Not located in restricted access locations.	N

2	PROTECTION FROM HAZARDS		N
2.1	Protection from electric shock and energy hazards		N
2.1.1	Protection in operator access areas	Class III appliance, no hazardous parts in operator access areas.	N
2.1.1.1	Access to energized parts	No energized parts	N
	Test by inspection .....		N
	Test with test finger (Figure 2A) .....		N
	Test with test pin (Figure 2B) .....		N
	Test with test probe (Figure 2C) .....		N
2.1.1.2	Battery compartments	No TNV circuit inside of the equipment	N
2.1.1.3	Access to ELV wiring	No ELV wiring in operator accessible area.	N
	Working voltage ( $V_{peak}$ or $V_{rms}$ ); minimum distance through insulation (mm)		—
2.1.1.4	Access to hazardous voltage circuit wiring	No hazardous voltage wiring in operator accessible area.	N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.1.1.5	Energy hazards .....	No hazardous energy level in operator accessible area.	N
2.1.1.6	Manual controls	No conductive shafts of operating knobs and handles.	N
2.1.1.7	Discharge of capacitors in equipment	Class III appliance	N
	Measured voltage (V); time-constant (s) .....		—
2.1.1.8	Energy hazards – d.c. mains supply		N
	a) Capacitor connected to the d.c. mains supply:		N
	b) Internal battery connected to the d.c. mains supply .....		N
2.1.1.9	Audio amplifiers .....		N
2.1.2	Protection in service access areas		N
2.1.3	Protection in restricted access locations	The unit is not limited to be used in restricted access locations.	N

2.2	SELV circuits		P
2.2.1	General requirements	See below.	N
2.2.2	Voltages under normal conditions (V) .....	Supplied by SELV from approved adapter.	P
2.2.3	Voltages under fault conditions (V) .....	Supplied by SELV from approved adapter.	P
2.2.4	Connection of SELV circuits to other circuits ...	See 1.5.7, 2.2.2 and 2.2.3. No direct connection between SELV and any primary circuits.	P

2.3	TNV circuits		N
2.3.1	Limits	No TNV circuits.	N
	Type of TNV circuits .....		—
2.3.2	Separation from other circuits and from accessible parts		N
2.3.2.1	General requirements		N
2.3.2.2	Protection by basic insulation		N
2.3.2.3	Protection by earthing		N
2.3.2.4	Protection by other constructions .....		N
2.3.3	Separation from hazardous voltages		N
	Insulation employed.....		—
2.3.4	Connection of TNV circuits to other circuits		N
	Insulation employed.....		—



EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

2.3.5	Test for operating voltages generated externally		N
-------	--	--	---

2.4	Limited current circuits		N
2.4.1	General requirements		N
2.4.2	Limit values		N
	Frequency (Hz) .....		—
	Measured current (mA).....		—
	Measured voltage (V) .....		—
	Measured circuit capacitance (nF or $\mu$ F) .....	--	—
2.4.3	Connection of limited current circuits to other circuits		N

2.5	Limited power sources		N
	a) Inherently limited output		N
	b) Impedance limited output		N
	c) Regulating network limited output under normal operating and single fault condition		N
	d) Overcurrent protective device limited output		N
	Max. output voltage (V), max. output current (A), max. apparent power (VA).....		—
	Current rating of overcurrent protective device (A)		—
	Use of integrated circuit (IC) current limiters (IEC/EN 60950-1 /A1)		N

2.6	Provisions for earthing and bonding		N
2.6.1	Protective earthing	Class III appliance, no protective earthing	N
2.6.2	Functional earthing		N
2.6.3	Protective earthing and protective bonding conductors	See below.	N
2.6.3.1	General		N
2.6.3.2	Size of protective earthing conductors		N
	Rated current (A), cross-sectional area ( $\text{mm}^2$ ), AWG .....		—
2.6.3.3	Size of protective bonding conductors		N
	Rated current (A), cross-sectional area ( $\text{mm}^2$ ), AWG .....		—
2.6.3.4	Resistance of earthing conductors and their terminations; resistance ( $\Omega$ ), voltage drop (V), test current (A), duration (min).....		N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
2.6.3.5	Colour of insulation .....		N
2.6.4	Terminals		N
2.6.4.1	General		N
2.6.4.2	Protective earthing and bonding terminals		N
	Rated current (A), type, nominal thread diameter (mm).....		—
2.6.4.3	Separation of the protective earthing conductor from protective bonding conductors		N
2.6.5	Integrity of protective earthing		N
2.6.5.1	Interconnection of equipment		N
2.6.5.2	Components in protective earthing conductors and protective bonding conductors		N
2.6.5.3	Disconnection of protective earth		N
2.6.5.4	Parts that can be removed by an operator		N
2.6.5.5	Parts removed during servicing		N
2.6.5.6	Corrosion resistance		N
2.6.5.7	Screws for protective bonding		N
2.6.5.8	Reliance on telecommunication network or cable distribution system		N
2.7	Overcurrent and earth fault protection in primary circuits		P
2.7.1	Basic requirements	Class III appliance	P
	Instructions when protection relies on building installation		N
2.7.2	Faults not simulated in 5.3.7		P
2.7.3	Short-circuit backup protection		P
2.7.4	Number and location of protective devices .....		P
2.7.5	Protection by several devices		N
2.7.6	Warning to service personnel .....		N
2.8	Safety interlocks		N
2.8.1	General principles	No safety interlocks	N
2.8.2	Protection requirements		N
2.8.3	Inadvertent reactivation		N
2.8.4	Fail-safe operation		N
	Protection against extreme hazard (IEC/EN 60950-1 /A1)		N
2.8.5	Moving parts		N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

2.8.6	Overriding		N
2.8.7	Switches and relays and their related circuits (IEC/EN 60950-1 /A1)		N
2.8.7.1	Separation distances for contact gaps and their related circuits (mm) (IEC/EN 60950-1 /A1)..... :		N
2.8.7.2	Overload test		N
2.8.7.3	Endurance test		N
2.8.7.4	Electric strength test		N
2.8.8	Mechanical actuators		N

2.9	Electrical insulation		P
2.9.1	Properties of insulating materials		P
2.9.2	Humidity conditioning		N
	Relative humidity (%), temperature (°C) ..... :		—
2.9.3	Grade of insulation	Functional insulation only, see clause 5.3.4	P
2.9.4	Separation from hazardous voltages		N
	Method(s) used ..... :		—

2.10	Clearances, creepage distances and distances through insulation		N
2.10.1	General		N
2.10.1.1	Frequency ..... :		N
2.10.1.2	Pollution degrees ..... :		N
2.10.1.3	Reduced values for functional insulation		N
2.10.1.4	Intervening unconnected conductive parts		N
2.10.1.5	Insulation with varying dimensions		N
2.10.1.6	Special separation requirements		N
2.10.1.7	Insulation in circuits generating starting pulses		N
2.10.2	Determination of working voltage		N
2.10.2.1	General		N
2.10.2.2	RMS working voltage		N
2.10.2.3	Peak working voltage		N
2.10.3	Clearances		N
2.10.3.1	General		N
2.10.3.2	Mains transient voltages		N
	a) AC mains supply ..... :		N
	b) Earthed d.c. mains supplies ..... :		N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	c) Unearthed d.c. mains supplies .....		N
	d) Battery operation .....		N
2.10.3.3	Clearances in primary circuits		N
2.10.3.4	Clearances in secondary circuits		N
2.10.3.5	Clearances in circuits having starting pulses	No such starting pulses	N
2.10.3.6	Transients from a.c. mains supply .....		N
2.10.3.7	Transients from d.c. mains supply .....		N
2.10.3.8	Transients from telecommunication networks and cable distribution systems .....		N
2.10.3.9	Measurement of transient voltage levels		-
	a) Transients from a mains supply		-
	For an a.c. mains supply .....		-
	For a d.c. mains supply .....		-
	b) Transients from a telecommunication network :		-
2.10.4	Creepage distances		N
2.10.4.1	General		N
2.10.4.2	Material group and comparative tracking index		N
	CTI tests .....		—
2.10.4.3	Minimum creepage distances		N
2.10.5	Solid insulation		N
2.10.5.1	General		N
2.10.5.2	Distances through insulation		N
2.10.5.3	Insulating compound as solid insulation		N
2.10.5.4	Semiconductor devices		N
2.10.5.5	Cemented joints		N
2.10.5.6	Thin sheet material – General		N
2.10.5.7	Separable thin sheet material		N
	Number of layers (pcs) .....		—
2.10.5.8	Non-separable thin sheet material		N
2.10.5.9	Thin sheet material – standard test procedure		N
	Electric strength test		—
2.10.5.10	Thin sheet material – alternative test procedure		N
	Electric strength test		—
2.10.5.11	Insulation in wound components		N
2.10.5.12	Wire in wound components		N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Working voltage .....		N
	a) Basic insulation not under stress .....		N
	b) Basic, supplementary, reinforced insulation ...		N
	c) Compliance with Annex U .....		N
	Two wires in contact inside wound component; angle between 45° and 90° .....		N
2.10.5.13	Wire with solvent-based enamel in wound components		N
	Electric strength test		—
	Routine test		N
2.10.5.14	Additional insulation in wound components		N
	Working voltage .....		N
	- Basic insulation not under stress .....		N
	- Supplementary, reinforced insulation .....		N
2.10.6	Construction of printed boards		N
2.10.6.1	Uncoated printed boards		N
2.10.6.2	Coated printed boards		N
2.10.6.3	Insulation between conductors on the same inner surface of a printed board		N
2.10.6.4	Insulation between conductors on different layers of a printed board		N
	Distance through insulation		N
	Number of insulation layers (pcs) .....		N
2.10.7	Component external terminations		N
2.10.8	Tests on coated printed boards and coated components		N
2.10.8.1	Sample preparation and preliminary inspection		N
2.10.8.2	Thermal conditioning		N
2.10.8.3	Electric strength test		N
2.10.8.4	Abrasion resistance test		N
2.10.9	Thermal cycling		N
2.10.10	Test for Pollution Degree 1 environment and insulating compound		N
2.10.11	Tests for semiconductor devices and cemented joints		N
2.10.12	Enclosed and sealed parts	No such parts	N
3	WIRING, CONNECTIONS AND SUPPLY		P

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
3.1	General		P
3.1.1	Current rating and overcurrent protection	Internal wiring gauge is suitable for current intended to be carried. SELV circuit only, overcurrent protective device was not required.	P
3.1.2	Protection against mechanical damage	Wires do not touch sharp edges and heatsinks which could damage the insulation and cause hazards.	P
3.1.3	Securing of internal wiring	Internal wires secured by connectors so that a loosening of terminations unlikely.	P
3.1.4	Insulation of conductors		N
3.1.5	Beads and ceramic insulators	Not used	N
3.1.6	Screws for electrical contact pressure	No such screws	N
3.1.7	Insulating materials in electrical connections	No such material	N
3.1.8	Self-tapping and spaced thread screws	No self-tapping screws are used.	N
3.1.9	Termination of conductors		N
	10 N pull test		N
3.1.10	Sleeving on wiring		N

3.2	Connection to a mains supply		N
3.2.1	Means of connection		N
3.2.1.1	Connection to an a.c. mains supply		N
3.2.1.2	Connection to a d.c. mains supply		N
3.2.2	Multiple supply connections		N
3.2.3	Permanently connected equipment		N
	Number of conductors, diameter of cable and conduits (mm) .....		—
3.2.4	Appliance inlets		N
3.2.5	Power supply cords		N
3.2.5.1	AC power supply cords		N
	Type .....		—
	Rated current (A), cross-sectional area (mm <sup>2</sup> ), AWG .....		—
3.2.5.2	DC power supply cords		N
3.2.6	Cord anchorages and strain relief		N
	Mass of equipment (kg), pull (N) .....		—

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	Longitudinal displacement (mm) .....		—
3.2.7	Protection against mechanical damage		N
3.2.8	Cord guards		N
	Diameter or minor dimension D (mm); test mass (g) .....		—
	Radius of curvature of cord (mm) .....		—
3.2.9	Supply wiring space		N

3.3	Wiring terminals for connection of external conductors		N
3.3.1	Wiring terminals	Class III appliance, no such wiring terminals.	N
3.3.2	Connection of non-detachable power supply cords		N
3.3.3	Screw terminals		N
3.3.4	Conductor sizes to be connected		N
	Rated current (A), cord/cable type, cross-sectional area (mm <sup>2</sup> ).....		—
3.3.5	Wiring terminal sizes		N
	Rated current (A), type, nominal thread diameter (mm) .....		—
3.3.6	Wiring terminal design		N
3.3.7	Grouping of wiring terminals		N
3.3.8	Stranded wire		N

3.4	Disconnection from the mains supply		N
3.4.1	General requirement	Class III equipment, Connect to the mains via a adapter.	N
3.4.2	Disconnect devices	Integrated mains plug	N
3.4.3	Permanently connected equipment		N
3.4.4	Parts which remain energized		N
3.4.5	Switches in flexible cords		N
3.4.6	Number of poles - single-phase and d.c. equipment	Both poles disconnected simultaneously	N
3.4.7	Number of poles - three-phase equipment		N
3.4.8	Switches as disconnect devices		N
3.4.9	Plugs as disconnect devices		N
3.4.10	Interconnected equipment		N
3.4.11	Multiple power sources		N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

3.5	Interconnection of equipment		P
3.5.1	General requirements	Interconnection circuits are SELV circuits.	P
3.5.2	Types of interconnection circuits .....	Interconnection for SELV circuit	P
3.5.3	ELV circuits as interconnection circuits	No ELV interconnections	N
3.5.4	Data ports for additional equipment		N

4	PHYSICAL REQUIREMENTS		P
4.1	Stability		N
	Angle of 10°	<7kg	N
	Test force (N) .....		N

4.2	Mechanical strength		N
4.2.1	General		N
	Rack-mounted equipment (IEC/EN 60950-1 /A1)		N
4.2.2	Steady force test, 10 N		N
4.2.3	Steady force test, 30 N		N
4.2.4	Steady force test, 250 N		N
4.2.5	Impact test		N
	Fall test		N
	Swing test		N
4.2.6	Drop test; height (mm) .....		N
4.2.7	Stress relief test		N
4.2.8	Cathode ray tubes	No CRT provided.	N
	Picture tube separately certified .....		N
4.2.9	High pressure lamps	No high pressure lamps provided.	N
4.2.10	Wall or ceiling mounted equipment; force (N) ..		N
4.2.11	Rotating solid media (IEC/EN 60950-1 /A1)		N
	Test to cover on the door.....		N

4.3	Design and construction		P
4.3.1	Edges and corners	Edges or corners are rounded.	P
4.3.2	Handles and manual controls; force (N) .....		N



EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.3.3	Adjustable controls	No adjustable controls provided.	N
4.3.4	Securing of parts	Mechanical fixings in such a way designed that they will withstand mechanical stress occurring in normal use.	P
4.3.5	Connection by plugs and sockets		N
4.3.6	Direct plug-in equipment		N
	Torque .....		N
	Compliance with the relevant mains plug standard .....		N
4.3.7	Heating elements in earthed equipment		N
4.3.8	Batteries		N
	- Overcharging of a rechargeable battery		N
	- Unintentional charging of a non-rechargeable battery		N
	- Reverse charging of a rechargeable battery		N
	- Excessive discharging rate for any battery		N
4.3.9	Oil and grease	No Oil and grease.	N
4.3.10	Dust, powders, liquids and gases	Equipment in intended use not considered to be exposed to these.	N
4.3.11	Containers for liquids or gases	No container for liquids or gases provided.	N
4.3.12	Flammable liquids .....	The equipment does not contain flammable liquid.	N
	Quantity of liquid (l) .....		N
	Flash point (°C) .....		N
4.3.13	Radiation		N
4.3.13.1	General		N
4.3.13.2	Ionizing radiation	No ionizing radiation	N
	Measured radiation (pA/kg) .....		—
	Measured high-voltage (kV) .....		—
	Measured focus voltage (kV) .....		—
	CRT markings .....		—
4.3.13.3	Effect of ultraviolet (UV) radiation on materials	No ultraviolet radiation	N
	Part, property, retention after test, flammability classification .....		N
4.3.13.4	Human exposure to ultraviolet (UV) radiation ..		N
4.3.13.5	Lasers (including laser diodes) and LEDs (IEC/EN 60950-1 /A1)		N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
4.3.13.5.1	Lasers (including laser laser diodes)		N
	Laser class .....		—
4.3.13.5.2	Light emitting diodes (LEDs)		N
4.3.13.6	Other types .....		N
4.4	Protection against hazardous moving parts		N
4.4.1	General		N
4.4.2	Protection in operator access areas .....		N
	Household and home/office document/media shredders (IEC/EN 60950-1 /A1)	(see Annex EE)	N
4.4.3	Protection in restricted access locations .....	No such locations	N
4.4.4	Protection in service access areas		N
4.4.5	Protection against moving fan blades (IEC/EN 60950-1 /A1)		N
4.4.5.1	General		N
	Not considered to cause pain or injury. a).....:		N
	Is considered to cause pain, not injury b) .....		N
	Considered to cause injury c) .....		N
4.4.5.2	Protection for users		N
	Use of symbol or warning .....		N
4.4.5.3	Protection for service persons		N
	Use of symbol or warning .....		N
4.5	Thermal requirements		P
4.5.1	General		P
4.5.2	Temperature tests		P
	Normal load condition per Annex L .....	Rated load with continuous operation.	—
4.5.3	Temperature limits for materials	(see appended table 4.5)	P
4.5.4	Touch temperature limits	(see appended table 4.5)	P
4.5.5	Resistance to abnormal heat .....	(see appended table 4.5)	P
4.6	Openings in enclosures		P
4.6.1	Top and side openings	No openings	N
	Dimensions (mm) .....		—
4.6.2	Bottoms of fire enclosures	Transportable appliance, not	N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

		applicable	
	Construction of the bottommm, dimensions (mm) :		—
4.6.3	Doors or covers in fire enclosures	No doors or covers	N
4.6.4	Openings in transportable equipment		N
4.6.4.1	Constructional design measures		N
	Dimensions (mm) ..... :		—
4.6.4.2	Evaluation measures for larger openings	No larger openings	N
4.6.4.3	Use of metallized parts		N
4.6.5	Adhesives for constructional purposes		N
	Conditioning temperature (°C), time (weeks) .... :		—

4.7	Resistance to fire		P
4.7.1	Reducing the risk of ignition and spread of flame	Use of materials with the required flammability classes.	P
	Method 1, selection and application of components wiring and materials		P
	Method 2, application of all of simulated fault condition tests		N
4.7.2	Conditions for a fire enclosure		P
4.7.2.1	Parts requiring a fire enclosure		P
4.7.2.2	Parts not requiring a fire enclosure		N
4.7.3	Materials		P
4.7.3.1	General	Components mounted on PCB with flammability V-0.	P
4.7.3.2	Materials for fire enclosures	Metal Enclosure	P
4.7.3.3	Materials for components and other parts outside fire enclosures		N
4.7.3.4	Materials for components and other parts inside fire enclosures	Other components of table 1.5.1	N
4.7.3.5	Materials for air filter assemblies	No air filter assemblies.	N
4.7.3.6	Materials used in high-voltage components	No high voltage component.	N

5	ELECTRICAL REQUIREMENTS AND SIMULATED ABNORMAL CONDITIONS		P
5.1	Touch current and protective conductor current		N
5.1.1	General	Class III equipment	N
5.1.2	Configuration of equipment under test (EUT)		N
5.1.2.1	Single connection to an a.c. mains supply		N
5.1.2.2	Redundant multiple connections to an a.c. mains	See above	N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

	supply		
5.1.2.3	Simultaneous multiple connections to an a.c. mains supply	See above	N
5.1.3	Test circuit		N
5.1.4	Application of measuring instrument		N
5.1.5	Test procedure		N
5.1.6	Test measurements		N
	Supply voltage (V) .....		—
	Measured touch current (mA) .....		—
	Max. allowed touch current (mA) .....		—
	Measured protective conductor current (mA) ...		—
	Max. allowed protective conductor current (mA):		—
5.1.7	Equipment with touch current exceeding 3,5 mA		N
5.1.7.1	General .....		N
5.1.7.2	Simultaneous multiple connections to the supply		N
5.1.8	Touch currents to telecommunication networks and cable distribution systems and from telecommunication networks	No TNV.	N
5.1.8.1	Limitation of the touch current to a telecommunication network or to a cable distribution system	Ditto.	N
	Supply voltage (V) .....	Ditto.	—
	Measured touch current (mA) .....	Ditto.	—
	Max. allowed touch current (mA) .....	Ditto.	—
5.1.8.2	Summation of touch currents from telecommunication networks	No TNV.	N
	a) EUT with earthed telecommunication ports .:		N
	b) EUT whose telecommunication ports have no reference to protective earth		N

5.2	Electric strength		N
5.2.1	General		N
5.2.2	Test procedure	(see appended table 5.2)	N

5.3	Abnormal operating and fault conditions		P
5.3.1	Protection against overload and abnormal operation	(see appended table 5.3)	P
5.3.2	Motors	No Motors	N
5.3.3	Transformers		P

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

5.3.4	Functional insulation .....	(see appended table 5.3)	P
5.3.5	Electromechanical components	No electromechanical component	N
5.3.6	Audio amplifiers in ITE .....	See appended table 5.3	P
5.3.7	Simulation of faults	Result see appended table 5.3	P
5.3.8	Unattended equipment		N
5.3.9	Compliance criteria for abnormal operating and fault conditions	See below	P
5.3.9.1	During the tests	No fire propagated beyond the equipment.	P
5.3.9.2	After the tests	No hazards	P

6	CONNECTION TO TELECOMMUNICATION NETWORKS		N
6.1	Protection of telecommunication network service persons, and users of other equipment connected to the network, from hazards in the equipment		N
6.1.1	Protection from hazardous voltages		N
6.1.2	Separation of the telecommunication network from earth		N
6.1.2.1	Requirements		N
	Supply voltage (V) .....		—
	Current in the test circuit (mA) .....		—
6.1.2.2	Exclusions .....		N

6.2	Protection of equipment users from overvoltages on telecommunication networks		N
6.2.1	Separation requirements		N
6.2.2	Electric strength test procedure		N
6.2.2.1	Impulse test		N
6.2.2.2	Steady-state test		N
6.2.2.3	Compliance criteria		N

6.3	Protection of the telecommunication wiring system from overheating		N
	Max. output current (A) .....		—
	Current limiting method .....		—

7	CONNECTION TO CABLE DISTRIBUTION SYSTEMS		N
7.1	General		N
7.2	Protection of cable distribution system service persons, and users of other equipment connected to the system, from hazardous		N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	voltages in the equipment		
7.3	Protection of equipment users from overvoltages on the cable distribution system		N
7.4	Insulation between primary circuits and cable distribution systems		N
7.4.1	General		N
7.4.2	Voltage surge test		N
7.4.3	Impulse test		N

A	ANNEX A, TESTS FOR RESISTANCE TO HEAT AND FIRE		N
A.1	Flammability test for fire enclosures of movable equipment having a total mass exceeding 18 kg, and of stationary equipment (see 4.7.3.2) <i>UL approved material used. No further tests were considered.</i>		N
A.1.1	Samples .....		—
	Wall thickness (mm) .....		—
A.1.2	Conditioning of samples; temperature (°C) .....		N
A.1.3	Mounting of samples .....		N
A.1.4	Test flame (see IEC 60695-11-3)		N
	Flame A, B, C or D .....		—
A.1.5	Test procedure		N
A.1.6	Compliance criteria		N
	Sample 1 burning time (s) .....		—
	Sample 2 burning time (s) .....		—
	Sample 3 burning time (s) .....		—
A.2	Flammability test for fire enclosures of movable equipment having a total mass not exceeding 18 kg, and for material and components located inside fire enclosures (see 4.7.3.2 and 4.7.3.4)		N
A.2.1	Samples, material .....		—
	Wall thickness (mm) .....		—
A.2.2	Conditioning of samples; temperature (°C) .....		N
A.2.3	Mounting of samples .....		N
A.2.4	Test flame (see IEC 60695-11-4)		N
	Flame A, B or C .....		—
A.2.5	Test procedure		N
A.2.6	Compliance criteria		N
	Sample 1 burning time (s) .....		—

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
	Sample 2 burning time (s) .....		—
	Sample 3 burning time (s) .....		—
A.2.7	Alternative test acc. To IEC 60695-11-5, cl. 5 and 9		N
	Sample 1 burning time (s) .....		—
	Sample 2 burning time (s) .....		—
	Sample 3 burning time (s) .....		—
A.3	Hot flaming oil test (see 4.6.2)		N
A.3.1	Mounting of samples		N
A.3.2	Test procedure		N
A.3.3	Compliance criterion		N

B	ANNEX B, MOTOR TESTS UNDER ABNORMAL CONDITIONS (see 4.7.2.2 and 5.3.2)		P
B.1	General requirements	See below.	P
	Position .....	Fixed on internal enclosure	—
	Manufacturer .....	See component list.	—
	Type .....	Ditto	—
	Rated values .....	Ditto	—
B.2	Test conditions		P
B.3	Maximum temperatures		P
B.4	Running overload test	DC motor in secondary circuit	N
B.5	Locked-rotor overload test	Ditto	N
	Test duration (days) .....		—
	Electric strength test: test voltage (V) .....		—
B.6	Running overload test for d.c. motors in secondary circuits	electronic drive circuits, no test required	N
B.6.1	General		N
B.6.2	Test procedure		N
B.6.3	Alternative test procedure		N
B.6.4	Electric strength test; test voltage (V) .....		N
B.7	Locked-rotor overload test for d.c. motors in secondary circuits		P
B.7.1	General		P
B.7.2	Test procedure		P
B.7.3	Alternative test procedure		N
B.7.4	Electric strength test; test voltage (V) .....		N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
B.8	Test for motors with capacitors		N
B.9	Test for three-phase motors		N
B.10	Test for series motors	Not series motor	N
	Operating voltage (V) ..... :		—

C	ANNEX C, TRANSFORMERS (see 1.5.4 and 5.3.3)		N
	Position ..... :		—
	Manufacturer ..... :		—
	Type ..... :		—
	Rated values ..... :		—
	Method of protection ..... :		—
C.1	Overload test		N
C.2	Insulation		N
	Protection from displacement of windings ..... :		N

D	ANNEX D, MEASURING INSTRUMENTS FOR TOUCH-CURRENT TESTS (see 5.1.4)		N
D.1	Measuring instrument		N
D.2	Alternative measuring instrument		N

E	ANNEX E, TEMPERATURE RISE OF A WINDING (see 1.4.13)		N
---	---	--	---

F	ANNEX F, MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES (see 2.10 and Annex G)		N
---	--	--	---

G	ANNEX G, ALTERNATIVE METHOD FOR DETERMINING MINIMUM CLEARANCES		N
G.1	Clearances		N
G.1.1	General		N
G.1.2	Summary of the procedure for determining minimum clearances		N
G.2	Determination of mains transient voltage (V)		N
G.2.1	AC mains supply ..... :		N
G.2.2	Earthed d.c. mains supplies ..... :		N
G.2.3	Unearthed d.c. mains supplies ..... :		N
G.2.4	Battery operation ..... :		N
G.3	Determination of telecommunication network transient voltage (V) ..... :		N



EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
G.4	Determination of required withstand voltage (V)		N
G.4.1	Mains transients and internal repetitive peaks .. :		N
G.4.2	Transients from telecommunication networks .. :		N
G.4.3	Combination of transients		N
G.4.4	Transients from cable distribution systems		N
G.5	Measurement of transient voltages (V)		N
	a) Transients from a mains supply		N
	For an a.c. mains supply		N
	For a d.c. mains supply		N
	b) Transients from a telecommunication network		N
G.6	Determination of minimum clearances ..... :		N
H	ANNEX H, IONIZING RADIATION (see 4.3.13)		N
J	ANNEX J, TABLE OF ELECTROCHEMICAL POTENTIALS (see 2.6.5.6)		N
	Metal(s) used ..... :		—
K	ANNEX K, THERMAL CONTROLS (see 1.5.3 and 5.3.8)		N
K.1	Making and breaking capacity		N
K.2	Thermostat reliability; operating voltage (V) ..... :		N
K.3	Thermostat endurance test; operating voltage (V) ..... :		N
K.4	Temperature limiter endurance; operating voltage (V) ..... :		N
K.5	Thermal cut-out reliability		N
K.6	Stability of operation		N
L	ANNEX L, NORMAL LOAD CONDITIONS FOR SOME TYPES OF ELECTRICAL BUSINESS EQUIPMENT (see 1.2.2.1 and 4.5.2)		P
L.1	Typewriters		N
L.2	Adding machines and cash registers		N
L.3	Erasers		N
L.4	Pencil sharpeners		N
L.5	Duplicators and copy machines		N
L.6	Motor-operated files		N
L.7	Other business equipment	Continuous operation	P

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
M	ANNEX M, CRITERIA FOR TELEPHONE RINGING SIGNALS (see 2.3.1)		N
M.1	Introduction		N
M.2	Method A		N
M.3	Method B		N
M.3.1	Ringing signal		N
M.3.1.1	Frequency (Hz) .....		—
M.3.1.2	Voltage (V) .....		—
M.3.1.3	Cadence; time (s), voltage (V) .....		—
M.3.1.4	Single fault current (mA) .....		—
M.3.2	Tripping device and monitoring voltage .....		N
M.3.2.1	Conditions for use of a tripping device or a monitoring voltage		N
M.3.2.2	Tripping device		N
M.3.2.3	Monitoring voltage (V) .....		N
N	ANNEX N, IMPULSE TEST GENERATORS (see 1.5.7.2, 1.5.7.3, 2.10.3.9, 6.2.2.1, 7.3.2, 7.4.3 and Clause G.5)		N
N.1	ITU-T impulse test generators		N
N.2	IEC 60065 impulse test generator		N
P	ANNEX P, NORMATIVE REFERENCES		—
Q	ANNEX Q, Voltage dependent resistors (VDRs) (see 1.5.9.1)		N
	a) Preferred climatic categories .....		N
	b) Maximum continuous voltage .....		N
	c) Pulse current .....		N
R	Annex R, EXAMPLES OF REQUIREMENTS FOR QUALITY CONTROL PROGRAMMES		N
R.1	Minimum separation distances for unpopulated coated printed boards (see 2.10.6.2)		N
R.2	Reduced clearances (see 2.10.3)		N
S	ANNEX S, PROCEDURE FOR IMPULSE TESTING (see 6.2.2.3)		N
S.1	Test equipment		N
S.2	Test procedure		N
S.3	Examples of waveforms during impulse testing		N

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
T	ANNEX T, GUIDANCE ON PROTECTION AGAINST INGRESS OF WATER (see 1.1.2)		N
U	ANNEX U, INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION (see 2.10.5.4)		N
V	ANNEX V, AC POWER DISTRIBUTION SYSTEMS (see 1.6.1)		N
V.1	Introduction		N
V.2	TN power distribution systems		N
W	ANNEX W, SUMMATION OF TOUCH CURRENTS		N
W.1	Touch current from electronic circuits		N
W.1.1	Floating circuits		N
W.1.2	Earthed circuits		N
W.2	Interconnection of several equipments		N
W.2.1	Isolation		N
W.2.2	Common return, isolated from earth		N
W.2.3	Common return, connected to protective earth		N
X	ANNEX X, MAXIMUM HEATING EFFECT IN TRANSFORMER TESTS (see clause C.1)		N
X.1	Determination of maximum input current		N
X.2	Overload test procedure		N
Y	ANNEX Y, ULTRAVIOLET LIGHT CONDITIONING TEST (see 4.3.13.3)		N
Y.1	Test apparatus .....		N
Y.2	Mounting of test samples .....		N
Y.3	Carbon-arc light-exposure apparatus .....		N
Y.4	Xenon-arc light exposure apparatus .....		N
Z	ANNEX Z, OVERVOLTAGE CATEGORIES (see 2.10.3.2 and Clause G.2)		P
AA	ANNEX AA, MANDREL TEST (see 2.10.5.8)		N
BB	ANNEX BB, CHANGES IN THE SECOND EDITION		—

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

CC	ANNEX CC, Evaluation of integrated circuit (IC) current limiters (IEC/EN 60950-1 /A1)		N
CC.1	General		N
CC.2	Test program 1 .....		N
CC.3	Test program 2 .....		N

DD	ANNEX DD, Requirements for the mounting means of rack-mounted equipment (IEC/EN 60950-1 /A1)		N
DD.1	General		N
DD.2	Mechanical strength test, variable N.....		N
DD.3	Mechanical strength test, 250N, including end stops.....		N
DD.4	Compliance.....		N

EE	ANNEX EE, Household and home/office document/media shredders (IEC/EN 60950-1 /A1)		N
EE.1	General		N
EE.2	Markings and instructions		N
	Use of markings or symbols.....		N
	Information of user instructions, maintenance and/or servicing instructions.....		N
EE.3	Inadvertent reactivation test.....		N
EE.4	Disconnection of power to hazardous moving parts:		N
	Use of markings or symbols.....		N
EE.5	Protection against hazardous moving parts		N
	Test with test finger (Figure 2A) .....		N
	Test with wedge probe (Figure EE1 and EE2) ...		N

EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMONMODIFICATIONS												
	Clauses, subclauses, notes, tables and figures which are additional to those inIEC60950-1 and it’s amendmets are prefixed “Z”			P								
Contents  (A2:2013)	Add the following annexes:  Annex ZA (normative) Normative references to internationalpublications with their corresponding Europeanpublications  Annex ZB (normative) Special national conditions  Annex ZD (informative)IEC and CENELEC code designations forflexible cords			P								
General	Delete all the “country” notes in the reference document (IEC 60950-1:2005)according to the following list:  1.4.8 Note 21.5.1 Note 2 & 31.5.7.1 Note  1.5.8 Note 2 1.5.9.4 Note 11.7.2.1 Note 4, 5 & 6  2.2.3 Note 22.2.4 Note 22.3.2 Note  2.3.2.1 Note 2 2.3.4 Note 2 2.6.3.3 Note 2 & 3 2.7.1 Note 210.3.2 Note 2 2.10.5.13 Note 3  3.2.1.1 Note 33.2.4 Note 33.2.5.1 Note 2  4.3.6 Note 1 & 2 4.7 Note 4 4.7.2.2 Note 47.3.1 Note 2 5.1.7.1 Note 3 & 4 5.3.7 Note 1  6 Note 2 & 5 6.1.2.1 Note 2 6.1.2.2 Note 62.2 Note 6. 2.2.1 Note 2 6.2.2.2 Note 7.1 Note 3 7.2 Note 7.3 Note 1 & 2  G.2.1 Note 2 Annex H Note 2			P								
General (A1:2010)	Delete all the “country” notes in the reference document(IEC 60950-1:2005/A1:2010) according to the following list: <table><tr><td>1.5.7.1</td><td>Note</td><td>6.1.2.1</td><td>Note 2</td></tr><tr><td>6.2.2.1</td><td>Note 2</td><td>EE.3</td><td>Note</td></tr></table>			1.5.7.1	Note	6.1.2.1	Note 2	6.2.2.1	Note 2	EE.3	Note	P
1.5.7.1	Note	6.1.2.1	Note 2									
6.2.2.1	Note 2	EE.3	Note									
General (A2:2013)	Delete all the “country” notes in the reference document (IEC 60950-1:2005/A2:2013) according to the following list:  2.7.1Note *2.10.3.1Note 2  6.2.2.Note			P								

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	*Note of secretary: Text of Common Modification remains unchanged.		
1.1.1 (A1:2010)	Replace the text of NOTE 3 by the following. NOTE 3 The requirements of EN 60065 may also be used to meet safety requirements for multimedia equipment. See IEC Guide 112, Guide on the safety of multimedia equipment. For television sets EN60065 applies.		P
1.3.Z1	<p>Add the following subclause:</p> <p>1.3.Z1 Exposure to excessive sound pressure The apparatus shall be so designed and constructed as to present no danger when used for its intended purpose, either in normal operating conditions or under fault conditions, particularly providing protection against exposure to excessive sound pressures from headphones or earphones.</p> <p>NOTE Z1 A new method of measurement is described in EN 50332-1, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations –</p> <p>Part 1: General method for “one package equipment”, and in EN 50332-2, Sound system equipment: Headphones and earphones associated with portable audio equipment - Maximum sound pressure level measurement methodology and limit considerations –</p> <p>Part 2: Guidelines to associate sets with headphones coming from different manufacturers.</p>		N/A
(A12:2011)	<p>In EN 60950-1:2006/A12:2011</p> <p>Delete the addition of 1.3.Z1 / EN 60950-1:2006</p> <p>Delete the definition 1.2.3.Z1 / EN 60950-1:2006 /A12:2010</p>		N/A
1.5.1 (Added info*)	<p>Add the following NOTE:</p> <p>NOTE Z1 The use of certain substances in electrical and electronic equipment is restricted within the EU: see Directive 2002/95/EC</p> <p>New Directive 2011/65/11 *</p>		N/A
1.7.2.1 (A1:2010)	In addition, for a PORTABLE SOUND SYSTEM, the instructions shall include a warning that excessive sound pressure from earphones and headphones can cause hearing loss.		N/A
1.7.2.1 (A12:2011)	<p>In EN 60950-1:2006/A12:2011</p> <p>Delete NOTE Z1 and the addition for Portable Sound System.</p> <p>Add the following clause and annex to the existing standard and amendments.</p>		N/A
	Zx Protection against excessive sound pressure from personal music players.		N/A
	Zx.1 General		N/A

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	<p>This sub-clause specifies requirements for protection against excessive sound pressure from personal music players that are closely coupled to the ear. It also specifies requirements for earphones and headphones intended for use with personal music players.</p> <p>A personal music player is a portable equipment for personal use, that:</p> <ul style="list-style-type: none"> <li>- is designed to allow the user to listen to recorded or broadcast sound or video; and</li> <li>- primarily uses headphones or earphones that can be worn in or on or around the ears; and</li> <li>- allows the user to walk around while in use.</li> </ul> <p>NOTE 1 Examples are hand-held or body-worn portable CD players, MP3 audio players, mobile phones with MP3 type features, PDA's or similar equipment.</p> <p>A personal music player and earphones or headphones intended to be used with personal music players shall comply with the requirements of this sub-clause.</p> <p>The requirements in this sub-clause are valid for music or video mode only.</p> <p>The requirements do not apply:</p> <ul style="list-style-type: none"> <li>-while the personal music players is connected to an external amplifier; or</li> <li>-while the headphones or earphones are not used.</li> </ul> <p>NOTE 2 An external amplifier which is not part of the personal music players or the listening device, but which is intended to play the music as a standalone music player.</p> <p>The requirements do not apply to:</p> <ul style="list-style-type: none"> <li>-hearing aid equipment and professional equipment;</li> </ul> <p>NOTE 3 Professional equipment is equipment sold through special sales channels. All products sold through normal electronics stores are considered not to be professional equipment.</p> <ul style="list-style-type: none"> <li>-analogue personal music players (personal music players without any kind of digital processing of the sound signal) that are brought to the market before the end of 2015.</li> </ul> <p>NOTE 4 This exemption has been allowed because this technology is falling out of use and it is expected that within a few years it will no longer exist. This exemption will not be extended to other technologies.</p> <p>For equipment which is clearly designed or</p>		
--	---	--	--

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	intended for use by young children, the limits of EN 71-1 apply.		
	<p>Zx.2 Equipment requirements</p> <p>No safety provision is required for equipment that complies with the following:</p> <ul style="list-style-type: none"> <li>-equipment provided as a package (personal music player with its listening device), where the acoustic output LAeq.T is <math>\leq 85</math> dBA measured while playing the fixed "programme simulation noise" as described in EN 50332-1; and</li> <li>-a personal music player provided with an analogue electrical output is <math>\leq 27</math> mV measured as described in EN 50332-2, while playing the fixed "programme simulation noise" as described in EN 50332-1.</li> </ul> <p>NOTE 1 wherever the term acoustic output is used in this clause, the 30 s A-weighted equivalent sound pressure level LAeq.T is meant. See also Zx.5 and Annex Zx.</p> <p>All other equipment shall:</p> <ul style="list-style-type: none"> <li>a) protect the user from unintentional acoustic outputs exceeding those mentioned above; and</li> <li>b) have a standard acoustic output level not exceeding those mentioned above, and automatically return to an output level not exceeding those mentioned above when the power is switched off; and</li> <li>c) provide a means to actively inform the user of the increased sound pressure when the equipment is operated with an acoustic output exceeding those mentioned above. Any means used shall be acknowledged by the user before activating a mode of operation which allows for an acoustic output exceeding those mentioned above. The acknowledgement does not need to be repeated more than once every 20 h of cumulative listening time; and</li> </ul> <p>NOTE 2 Examples of means include visual or audible signals. Action from the user is always required.</p> <p>NOTE 3 The 20 h listening time is the accumulative listening time, independent how long the personal music player has been switched off.</p> <ul style="list-style-type: none"> <li>d) have a warning as specified in Zx.3; and</li> <li>e) not exceed the following: <ul style="list-style-type: none"> <li>1) equipment provided as a package (player with its listening device), the acoustic output shall be <math>\leq 100</math> dBA measured while playing the fixed "programme simulation noise" described in EN 50332-1; and</li> </ul> </li> </ul>		N/A



EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	<p>2) a personal music player provided with an analogue electrical output socket for a listening device, the electrical output shall be <math>\leq 150</math> mV measured as described in EN 50332-2, while playing the fixed "programme simulation noise" described in EN 50332-1.</p> <p>For music where the average sound pressure (long term LAeq,T) measured over the duration of the song is lower than the average produced by the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA. In this case T becomes the duration of the song.</p> <p>NOTE 4 Classical music typically has an average sound pressure (long term LAeq,T) which is much lower than the average programme simulation noise. Therefore, if the player is capable to analyse the song and compare it with the programme simulation noise, the warning does not need to be given as long as the average sound pressure of the song is below the basic limit of 85 dBA.</p> <p>For example, if the player is set with the programme simulation noise to 85 dBA, but the average music level of the song is only 65 dBA, there is no need to give a warning or ask an acknowledgement as long as the average sound level of the song is not above the basic limit of 85 dBA.</p>		
	<p><b>Zx.3 Warning</b></p> <p>The warning shall be placed on the equipment, or on the packaging, or in the instruction manual and shall consist of the following:</p> <ul style="list-style-type: none"> <li>- The symbol of Figure 1 with a minimum height of 5 mm; and</li> <li>- The following wording, or similar: "To prevent possible hearing damage, do not listen at high volume levels for long periods."</li> </ul> <div data-bbox="558 1624 742 1803" data-label="Image"> </div> <p>Figure 1 – Warning label (IEC 60417-6044)</p> <p>Alternatively, the entire warning may be given through the equipment display during use, when the user is asked to acknowledge activation of the higher level.</p>		N/A
	<b>Zx.4 Requirements for listening devices (headphones and earphones)</b>		--

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	<p>Zx.4.1 Wired listening devices with analogue input</p> <p>With 94 dBA sound pressure output LAeq,T, the input voltage of the fixed "programme simulation noise" described in EN 50332-2 shall be <math>\geq 75</math> mV.</p> <p>This requirement is applicable in any mode where the headphones can operate (active or passive), including any available setting (for example built-in volume level control).</p> <p>NOTE The values of dBA -75 mV correspond with 85 dBA -27 mV and 100 dBA -150 mV.</p>		N/A
	<p>Zx.4.2 Wired listening devices with digital input</p> <p>With any playing device playing the fixed "programme simulation noise" described in EN 50332-1 (and respecting the digital interface standards, where a digital interface standard exists that specifies the equivalent acoustic level), the acoustic output LAeq,T of the listening device shall be <math>\leq 100</math> dBA.</p> <p>This requirement is applicable in any mode where the headphones can operate, including any available setting (for example built-in volume level control, additional sound feature like equalization, etc.).</p> <p>NOTE An example of a wired listening device with digital input is a USB headphone.</p>		N/A
	<p>Zx.4.3 Wireless listening devices</p> <p>In wireless mode:</p> <ul style="list-style-type: none"> <li>- with any playing and transmitting device playing the fixed programme simulation noise described in EN 50332-1; and</li> <li>- respecting the wireless transmission standards, where an air interface standard exists that specifies the equivalent acoustic level; and</li> <li>- with volume and sound settings in the listening device (for example built-in volume level control, additional sound feature like equalization, etc.) set to the combination of positions that maximize the measured acoustic output for the abovementioned programme simulation noise, the acoustic output LAeq,T of the listening device shall be <math>\leq 100</math> dBA</li> </ul> <p>NOTE An example of a wireless listening device is a Bluetooth headphone.</p>		N/A
	<p>Zx.5 Measurement methods</p> <p>Measurements shall be made in accordance with EN 50332-1 or EN 50332-2 as applicable. Unless stated otherwise, the time interval T shall be 30 s.</p> <p>NOTE Test method for wireless equipment</p>		N/A

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	provided without listening device should be defined.		
2.7.1	<p>Replace the subclause as follows:</p> <p>Basic requirements</p> <p>To protect against excessive current, short-circuits and earth faults in PRIMARY CIRCUITS, protective devices shall be included either as integral parts of the equipment or as parts of the building installation, subject to the following, a), b) and c):</p> <p>a) except as detailed in b) and c), protective devices necessary to comply with the requirements of 5.3 shall be included as parts of the equipment;</p> <p>b) for components in series with the mains input to the equipment such as the supply cord, appliance coupler, r.f.i. filter and switch, short-circuit and earth fault protection may be provided by protective devices in the building installation;</p>		P
	<p>c) it is permitted for PLUGGABLE EQUIPMENT TYPE B or PERMANENTLY CONNECTED EQUIPMENT, to rely on dedicated overcurrent and short-circuit protection in the building installation, provided that the means of protection, e.g. fuses or circuit breakers, is fully specified in the installation instructions. If reliance is placed on protection in the building installation, the installation instructions shall so state, except that for PLUGGABLE EQUIPMENT TYPE A the building installation shall be regarded as providing protection in accordance with the rating of the wall socket outlet.</p>		N/A
2.7.2	This subclause has been declared 'void'.		N/A
3.2.3	Delete the NOTE in Table 3A, and delete also in this table the conduit sizes in parentheses.		N/A
3.2.5.1	<p>Replace "60245 IEC 53" by "H05 RR-F",</p> <p>"60227 IEC 52" by "H03 VV-F or H03 VVH2-F",</p> <p>"60227 IEC 53" by "H05 VV-F or H05 VVH2-F2".</p> <p>In table 3B, replace the first four lines by the following:</p> <p>Up to and including 6  0,75 a)  </p> <p>Over 6; up to and including 10  (0,75)b) 1,0 </p> <p>Over 10 up to and including 16  (1,0)c) 1,5 </p> <p>In the conditions applicable to table 3B, delete the words "in some countries" in condition a).</p> <p>In NOTE 1, applicable to Table 3B, delete the second sentence.</p>		N/A
3.2.5.1 (A2:2013)	NOTE Z1 The harmonised code designations corresponding to the IEC cord types are given in Annex ZD		N/A

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

3.3.4	In Table 3D, delete the fourth line: conductor sizes for 10 to 13 A, and replace with the following: Over 10 up to and including 16   1,5 to 2,5   1,5 to 4   Delete the fifth line : conductor sizes for 13 to 16 A.		N/A
4.3.13.6 (A1:2010)	Replace the existing NOTE by the following: NOTE Z1 Attention is drawn to: 1999/519/EC: Council Recommendation on the limitation of exposure of the general public to electromagnetic fields 0 Hz to 300 GHz, and 2006/25/EC: Directive on the minimum health and safety requirements regarding the exposure of workers to risks arising from physical agents (artificial optical radiation).		N/A
	Standards taking into account mentioned Recommendation and Directive which demonstrate compliance with the applicable EU Directive are indicated in the OJEC.		N/A
Annex H	Replace the last paragraph of this annex by: At any point 10 cm from the surface of the operator access area, the dose rate shall not exceed 1 $\mu$ Sv/h (0,1 mR/h) (see note). Account is taken of the background level Replace the notes as follows: NOTE These values appear in Directive 96/29/Euratom. Delete NOTE 2.		N/A
Bibliography	Additional EN standards.		—
ZA	NORMATIVE REFERENCES TO INTERNATIONAL PUBLICATIONS WITH THEIR CORRESPONDING EUROPEAN PUBLICATIONS		—
ZB ANNEX (normative) SPECIAL NATIONAL CONDITIONS (EN)			
1.2.4.1	In Denmark, certain types of Class I appliances (see 3.2.1.1) may be provided with a plug not establishing earthing conditions when inserted into Danish socket-outlets.		N/A
1.2.13.14 (A11:2009)	In Norway and Sweden, for requirements see 1.7.2.1 and 7.3 of this annex		N/A
1.5.7.1 (A11:2009)	In Finland, Norway and Sweden, resistors bridging BASIC INSULATION in CLASS I PLUGGABLE EQUIPMENT TYPE A must comply with the requirements in 1.5.7.1. In addition when a single resistor is used, the resistor must withstand the resistor test in 1.5.7.2.		N/A
1.5.8	In Norway, due to the IT power system used (see		N/A

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	annex V, Figure V.7), capacitors are required to be rated for the applicable line-to-line voltage (230 V).		
1.5.9.4	In Finland, Norway and Sweden, the third dashed sentence is applicable only to equipment as defined in 6.1.2.2 of this annex.		N/A
1.7.2.1	<p>In Finland, Norway and Sweden, CLASS I PLUGGABLE EQUIPMENT TYPE A intended for connection to other equipment or a network shall, if safety relies on connection to protective earth or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment must be connected to an earthed mains socket-outlet. The marking text in the applicable countries shall be as follows:</p> <p>In Finland: "Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan"</p> <p>In Norway: "Apparatet må tilkoples jordet stikkontakt" In Sweden: "Apparaten skall anslutas till jordat uttag"</p>		N/A
1.7.2.1(A1 1:2009)	<p>In Norway and Sweden, the screen of the cable distribution system is normally not earthed at the entrance of the building and there is normally no equipotential bonding system within the building. Therefore the protective earthing of the building installation need to be isolated from the screen of a cable distribution system.</p> <p>It is however accepted to provide the insulation external to the equipment by an adapter or an interconnection cable with galvanic isolator, which may be provided by e.g. a retailer.</p> <p>The user manual shall then have the following or similar information in Norwegian and Swedish language respectively, depending on in what country the equipment is intended to be used in: "Equipment connected to the protective earthing of the building installation through the mains connection or through other equipment with a connection to protective earthing – and to a cable distribution system using coaxial cable, may in some circumstances create a fire hazard. Connection to a cable distribution system has therefore to be provided through a device providing electrical isolation below a certain frequency range (galvanic isolator, see EN 60728-11)."</p>		
	NOTE In Norway, due to regulation for installations of cable distribution systems, and in Sweden, a galvanic isolator shall provide electrical insulation below 5 MHz. The insulation shall withstand a dielectric strength of 1,5 kV r.m.s., 50 Hz or 60 Hz, for 1 min.		N/A

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	<p>Translation to Norwegian (the Swedish text will also be accepted in Norway): "Utstyr som er koplet til beskyttelsesjord via nettplugg og/eller via annet jordtilkoplet utstyr – og er tilkoplet et kabel-TV nett, kan forårsake brannfare. For å unngå dette skal det ved tilkopling av utstyret til kabel-TV nettet installeres en galvanisk isolator mellom utstyret og kabel-TV nettet." Translation to Swedish: "Utrustning som är kopplad till skyddsjord via jordat vägguttag och/eller via annan utrustning och samtidigt är kopplad till kabel-TV nät kan i vissa fall medföra risk för brand. För att undvika detta skall vid anslutning av utrustningen till kabel-TV nät galvanisk isolator finnas mellan utrustningen och kabel-TV nätet."</p>		
1.7.2.1 (A2:2013)	<p>In Denmark, CLASS I PLUGGABLE EQUIPMENT TYPE A intended for connection to other equipment or a network shall, if safety relies on connection to protective earth or if surge suppressors are connected between the network terminals and accessible parts, have a marking stating that the equipment must be connected to an earthed mains socket-outlet.</p> <p>The marking text in Denmark shall be as follows: In Denmark: "Apparatets stikprop skal tilsluttes en stikkontakt med jord, som giver forbindelse til stikproppens jord."</p>		N/A
1.7.5  1.7.5 (A11:2009)	<p>In Denmark, socket-outlets for providing power to other equipment shall be in accordance with the Heavy Current Regulations, Section 107-2-D1, Standard Sheet DK 1-3a, DK 1-5a or DK 1-7a, when used on Class I equipment. For STATIONARY EQUIPMENT the socket-outlet shall be in accordance with Standard Sheet DK 1-1b or DK 1-5a.</p> <p>For CLASS II EQUIPMENT the socket outlet shall be in accordance with Standard Sheet DKA 1-4a.</p>		N/A
1.7.5 (A2:2013)	<p>In Denmark, socket-outlets for providing power to other equipment shall be in accordance with the DS 60884-2-D1:2011.</p> <p>For class I equipment the following Standard Sheets are applicable: DK 1-3a, DK 1-1c, DK 1-1d, DK 1-5a or DK 1-7a, with the exception for STATIONARY EQUIPMENT where the socket-outlets shall be in accordance with Standard Sheet DK 1-1b, DK 1-1c, DK 1-1d or DK 1-5a.</p> <p>Socket outlets intended for providing power to Class II apparatus with a rated current of 2,5 A shall be in accordance with DS 60884-2-D1 standard sheet DKA 1-4a. Other current ratings socket outlets shall be in compliance with by DS 60884-2-D1 Standard</p>		N/A

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	Sheet DKA 1-3a or DKA 1-3b. Justification the Heavy Current Regulations, 6c		
2.2.4	In Norway, for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.3.2	In Finland, Norway and Sweden there are additional requirements for the insulation. See 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.3.4	In Norway, for requirements see 1.7.2.1, 6.1.2.1 and 6.1.2.2 of this annex.		N/A
2.6.3.3	In the United Kingdom, the current rating of the circuit shall be taken as 13 A, not 16 A.		N/A
2.7.1	In the United Kingdom, to protect against excessive currents and short-circuits in the PRIMARY CIRCUIT of DIRECT PLUG-IN EQUIPMENT, tests according to 5.3 shall be conducted, using an external protective device rated 30 A or 32 A. If these tests fail, suitable protective devices shall be included as integral parts of the DIRECT PLUG-IN EQUIPMENT, so that the requirements of 5.3 are met.		N/A
2.10.5.13	In Finland, Norway and Sweden, there are additional requirements for the insulation, see 6.1.2.1 and 6.1.2.2 of this annex.		N/A
3.2.1.1	In Switzerland, supply cords of equipment having a RATED CURRENT not exceeding 10 A shall be provided with a plug complying with SEV 1011 or IEC 60884-1 and one of the following dimension sheets: SEV 6532-2.1991 Plug Type 15 3P+N+PE 250/400 V, 10 A		N/A
	SEV 6533-2.1991 Plug Type 11 L+N 250 V, 10 A SEV 6534-2.1991 Plug Type 12 L+N+PE 250 V, 10 A  In general, EN 60309 applies for plugs for currents exceeding 10 A. However, a 16A plug and socket-outlet system is being introduced in Switzerland, the plugs of which are according to the following dimension sheets, published in February 1998: SEV 5932-2.1998 Plug Type 25, 3L+N+PE 230/400V, 16 A SEV 5933-2.1998 Plug Type 21, L+N, 250V, 16A SEV 5934-2.1998 Plug Type 23, L+N+PE 250V, 16 A		N/A
3.2.1.1	In Denmark, supply cords of single-phase equipment having a rated current not exceeding 13 A shall be provided with a plug according to the Heavy Current		N/A

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	<p>Regulations, Section 107-2-D1.</p> <p>CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a.</p> <p>If poly-phase equipment and single-phase equipment having a RATED CURRENT exceeding 13 A is provided with a supply cord with a plug, this plug shall be in accordance with the Heavy Current Regulations, Section 107-2-D1 or EN 60309-2.</p>		
3.2.1.1 (A2:2013)	<p>In Denmark, supply cords of single-phase equipment having a rated current not exceeding 13 A shall be provided with a plug according to DS 60884-2-D1.</p> <p>CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules shall be provided with a plug in accordance with standard sheet DK 2-1a or DK 2-5a.</p> <p>If a single-phase equipment having a RATED CURRENT exceeding 13 A or if a poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with the standard sheets DK 6-1a in DS 60884-2-D1 or EN 60309-2.</p> <p>Justification the Heavy Current Regulations, 6c</p>		N/A
3.2.1.1	<p>In Spain, supply cords of single-phase equipment having a rated current not exceeding 10 A shall be provided with a plug according to UNE 20315:1994.</p> <p>Supply cords of single-phase equipment having a rated current not exceeding 2,5 A shall be provided with a plug according to UNE-EN 50075:1993.</p> <p>CLASS I EQUIPMENT provided with socket-outlets with earth contacts or which are intended to be used in locations where protection against indirect contact is required according to the wiring rules, shall be provided with a plug in accordance with standard UNE 20315:1994.</p> <p>If poly-phase equipment is provided with a supply cord with a plug, this plug shall be in accordance with UNE-EN 60309-2.</p>		N/A
3.2.1.1	<p>In the United Kingdom, apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to BS 1363 by means of that flexible cable or cord and</p>		N/A



EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	<p>plug, shall be fitted with a 'standard plug' in accordance with Statutory Instrument 1768:1994 - The Plugs and Sockets etc.(Safety) Regulations 1994, unless exempted by those regulations.</p> <p>NOTE 'Standard plug' is defined in SI 1768:1994 and essentially means an approved plug conforming to BS 1363 or an approved conversion plug.</p>		
3.2.1.1	<p>In Ireland, apparatus which is fitted with a flexible cable or cord and is designed to be connected to a mains socket conforming to I.S. 411 by means of that flexible cable or cord and plug, shall be fitted with a 13 A plug in accordance with Statutory Instrument 525:1997 - National Standards Authority of Ireland (section 28) (13 A Plugs and Conversion Adaptors for Domestic Use) Regulations 1997.</p>		N/A
3.2.4	<p>In Switzerland, for requirements see 3.2.1.1 of this annex.</p>		N/A
3.2.5.1	<p>In the United Kingdom, a power supply cord with conductor of 1,25 mm<sup>2</sup> is allowed for equipment with a rated current over 10 A and up to and including 13 A.</p>		N/A
3.3.4	<p>In the United Kingdom, the range of conductor sizes of flexible cords to be accepted by terminals for equipment with a RATED CURRENT of over 10 A up to and including 13 A is:</p> <ul style="list-style-type: none"> <li>• 1,25 mm<sup>2</sup> to 1,5 mm<sup>2</sup> nominal cross-sectional area.</li> </ul>		N/A
4.3.6	<p>In the United Kingdom, the torque test is performed using a socket outlet complying with BS 1363 part 1:1995, including Amendment 1:1997 and Amendment 2:2003 and the plug part of DIRECT PLUG-IN EQUIPMENT shall be assessed to BS 1363: Part 1, 12.1, 12.2, 12.3, 12.9, 12.11, 12.12, 12.13, 12.16 and 12.17, except that the test of 12.17 is performed at not less than 125 °C. Where the metal earth pin is replaced by an Insulated Shutter Opening Device (ISOD), the requirements of clauses 22.2 and 23 also apply.</p>		N/A
4.3.6	<p>In Ireland, DIRECT PLUG-IN EQUIPMENT is known as plug similar devices. Such devices shall comply with Statutory Instrument 526:1997 - National Standards Authority of Ireland (Section 28) (Electrical plugs, plug similar devices and sockets for domestic use) Regulations, 1997.</p>		N/A
5.1.7.1	<p>In Finland, Norway and Sweden TOUCH CURRENT measurement results exceeding 3,5 mA r.m.s. are permitted only for the</p>		N/A

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	<p>following equipment:</p> <ul style="list-style-type: none"> <li>• STATIONARY PLUGGABLE EQUIPMENT TYPE A that <ul style="list-style-type: none"> <li>is intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, for example, in a telecommunication centre; and</li> <li>has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR; and</li> <li>is provided with instructions for the installation of that conductor by a SERVICE PERSON;</li> </ul> </li> <li>• STATIONARY PLUGGABLE EQUIPMENT TYPE B;</li> <li>• STATIONARY PERMANENTLY CONNECTED EQUIPMENT.</li> </ul>		
6.1.2.1 (A1:2010)	<p>In Finland, Norway and Sweden, add the following text between the first and second paragraph of the compliance clause:</p> <p>If this insulation is solid, including insulation forming part of a component, it shall at least consist of either</p> <ul style="list-style-type: none"> <li>- two layers of thin sheet material, each of which shall pass the electric strength test below, or</li> <li>- one layer having a distance through insulation of at least 0,4 mm, which shall pass the electric strength test below.</li> </ul> <p>Alternatively for components, there is no distance through insulation requirements for the insulation consisting of an insulating compound completely filling the casing, so that CLEARANCES and CREEPAGE DISTANCES do not exist, if the component passes the electric strength test in accordance with the compliance clause below and in addition</p> <ul style="list-style-type: none"> <li>- passes the tests and inspection criteria of 2.10.11 with an electric strength test of 1,5 kV multiplied by 1,6 (the electric strength test of 2.10.10 shall be performed using 1,5 kV), and</li> <li>- is subject to ROUTINE TESTING for electric strength during manufacturing, using a test voltage of 1,5 kV.</li> </ul>		N/A
	<p>It is permitted to bridge this insulation with an optocoupler complying with 2.10.5.4 b).</p> <p>It is permitted to bridge this insulation with a capacitor complying with EN 60384-14:2005, subclass Y2.</p> <p>A capacitor classified Y3 according to EN 60384-14:2005, may bridge this insulation under the</p>		N/A

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

**EN 60950-1:2006/A11:2009/A1:2010/A12:2011/A2:2013– CENELEC COMMON MODIFICATIONS**

	<p>following conditions:</p> <ul style="list-style-type: none"> <li>- the insulation requirements are satisfied by having a capacitor classified Y3 as defined by EN 60384-14, which in addition to the Y3 testing, is tested with an impulse test of 2,5 kV defined in EN 60950-1:2006, 6.2.2.1;</li> <li>- the additional testing shall be performed on all the test specimens as described in EN 60384-14;</li> <li>- the impulse test of 2,5 kV is to be performed before the endurance test in EN 60384-14, in the sequence of tests as described in EN 60384-14.</li> </ul>		
6.1.2.2	<p>In Finland, Norway and Sweden, the exclusions are applicable for PERMANENTLY CONNECTED EQUIPMENT, PLUGGABLE EQUIPMENT TYPE Band equipment intended to be used in a RESTRICTED ACCESS LOCATION where equipotential bonding has been applied, e.g. in a telecommunication centre, and which has provision for a permanently connected PROTECTIVE EARTHING CONDUCTOR and is provided with instructions for the installation of that conductor by a SERVICE PERSON.</p>		N/A
7.2	<p>In Finland, Norway and Sweden, for requirements see 6.1.2.1 and 6.1.2.2 of this annex.</p> <p>The term TELECOMMUNICATION NETWORK in 6.1.2 being replaced by the term CABLE DISTRIBUTION SYSTEM.</p>		N/A
7.3 (A11:2009)	<p>In Norway and Sweden, for requirements see 1.2.13.14 and 1.7.2.1 of this annex.</p>		N/A

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict

1.5.1	TABLE: List of critical components					P
Object/part No.	Manufacturer/ trademark	Type/model	Technical data	Standard (Edition / year)	Mark(s) of conformity <sup>1)</sup>	
PCB	(various)	(various)	V-0, 130°C, Min 1.2mm	UL 94	UL	
Enclosure	(various)	(various)	Metal,min 1.3mm	EN 60950-1	Test in the equip	
Internal wire	(various)	(various)	VW-1, 80°C, 300V Min. 28AWG	UL 758	UL	
Battery	(various)	(various)	3.7V 150mAh	IEC/EN 62133	CE	
<sup>1)</sup> An asterisk indicates a mark which assures the agreed level of surveillance						

1.5.1	TABLE: Opto Electronic Devices (IEC/EN 60950-1 /A1)		N
Manufacturer.....:		--	
Type.....:		--	
Separately tested.....:		--	
Bridging insulation.....:		--	
External creepage distance.....:		--	
Internal creepage distance.....:		--	
Distance through insulation.....:		--	
Tested under the following conditions.....:		--	
Input.....:		--	
Output.....:		--	
supplementary information:			

1.6.2 (1)	TABLE: Electrical data (in normal conditions)					P
U(V)/f(Hz)	I (A)	Irated (A)	P (W)	Fuse #	Ifuse (A)	Condition/status
5VDC	0.9	1A	--	--	--	Supplied by an adapter, the adapter rated output is 5VDC, 1A
Supplementary information:						

2.1.1.5 c) 1)	TABLE: Electrical data (in normal conditions) (IEC/EN 60950-1 /A1)					N
Voltage (rated) (V)	Current (rated) (A)	Voltage (max.) (V)	Current (max.) (A)	VA (max.) (VA)		
--	--	--	--	--		

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
Supplementary information:			

2.1.1.7	TABLE: discharge test			N
Condition	$\tau$ calculated (s)	$\tau$ measured (ms)	t u→ 0V (s)	Comments
--	--	--	--	--
Note:				

2.2.2	TABLE: Hazardous voltage measurement			N
Transformer	Location	max. Voltage		Voltage Limitation Component
		V peak	V d.c.	
--	--	--	--	--
Note:				

2.2.3	TABLE: SEL voltage measurement		N
Location		Voltage measured (V)	Comments
--		--	--
Note:			

2.4.2	TABLE: limited current circuit measurement				N
Location	Voltage (V)	Current (mA)	Freq. (kHz)	Limit (mA)	Comments
--	--	--	--	--	--
Notes:					

2.5	TABLE: limited power source measurement			N
		Limits	Measured	Verdict
According to Table 2B				
current (in A)		≤8	--	--
apparent power (in VA)		≤100	--	--
According to Table 2B				
current (in A)		≤8	--	--
apparent power (in VA)		≤100	--	--
According to Table 2B				

EN 60950-1			
Clause	Requirement + Test	Result - Remark	Verdict
current (in A)	$\leq 8$	--	--
apparent power (in VA)	$\leq 100$	--	--
According to Table 2B			
current (in A)	$\leq 8$	--	--
apparent power (in VA)	$\leq 100$	--	--

2.10.2	Table: working voltage measurement			N
Location		Peak voltage (V)	RMS voltage (V)	Comments
--		--	--	--
Note:				

2.10.3 and 2.10.4	TABLE: Clearance and creepage distance measurements						N
Clearance (cl) and creepage distance (cr) at/of/between:	U peak (V)	U r.m.s. (V)	Required cl (mm)	cl (mm)	Required cr (mm)	cr (mm)	
--	--	--	--	--	--	--	
Supplementary information:							

2.10.5	TABLE: Distance through insulation measurements				N
Distance through insulation (DTI) at/of:		U r.m.s. (V)	Test voltage (V)	Required di (mm)	di (mm)
--		--	--	--	--
Supplementary information:					

4.3.8	TABLE: battery charge/discharge for battery pack				N
Component	Test voltage(VDC)	Abnormal condition	Duration	Observations	
--	--	--	--	--	
--	--	--	--	--	

4.5-1	TABLE: Thermal requirements		P
	Supply voltage (V)	5VDC (adapter output)	—
Maximum measured temperature T of part/at:		T (°C)	Allowed Tmax (°C)
Buttons		30.6	85
Internla wire		34.8	80
Input wire		46.9	80



**Appendix**  
**Photo documentation**

**Photo 1**

☒ front

☐ rear

☐ right side

☐ left side

☐ top

☐ bottom

☐ internal



\*\*\*\*\*End of the report\*\*\*\*\*